

Lenovo ThinkVision T24-40 Monitor

Seamless Visuals, Powerful Performance.




Helps save power at work

Match your screen to your workflow with the ThinkVision T24-40 Monitor's 48Hz - 120Hz variable refresh rate¹, optimized for seamless visuals while saving energy.



Combines clear images and comprehensive connectivity

Enjoy clear, distortion-free visuals with the ThinkVision T24-40 Monitor's 23.8-inch In-Plane Switching panel technology which delivers premium, vibrant colors from any viewing angle. Get more connected and compatible with a wide range of devices on T24-40's USB hubs, unlocking greater productivity for your workflows.



Boosts efficiency with Fleet Management

Manage and control your monitor assets with Lenovo Display Fleet Manager (LDFM). This innovative software solution empowers IT managers with robust tools for streamlined asset management, efficient firmware upgrades, and centralized settings control.

Lenovo ThinkVision T24-40 Monitor

Display

Panel Size
23.8-inch

Screen Dimensions
535.0 mm x 310.1 mm

Panel Type
4-sided Ultra Thin,
In-Plane Switching

Active Area
527.0 mm x 296.5 mm

Backlight
WLED

Aspect Ratio
16:9

Resolution
1920 x 1080

Pixel Pitch
0.2745 mm x 0.2745 mm

**Dot/Pixel Per Inch
(DPI/PPI)**
95

**Viewing Angle
(H x V @ CR 10:1)**
178° / 178°

Response Time (G to G)
4ms (Extreme Mode),
6ms (Normal Mode)

Refresh Rate
48Hz – 120Hz

Brightness
250 cd/m²

Contrast Ratio (Typical)
1500:1

**Dynamic Contrast Ratio
(Typical)**
3M:1

**Color Gamut
(Coverage Ratio)**
99% sRGB (CIE 1931)
99% BT.709 (CIE 1931)

Color Support (Typical)
16.7 Million

Color Depth
8-bit (6+FRC)

Anti-glare
Yes

Connectivity

Video Signal

1 x HDMI 1.4²

1 x DP 1.2

1 x VGA

USB Upstream

1 x USB-B (USB 5Gbps / USB 3.2 Gen 1)³

USB Downstream

3 x USB-A (USB 5Gbps / USB 3.2 Gen 1,
1 x BC1.2)³

1 x USB-C⁴ (USB 5Gbps / USB 3.2 Gen 1,
Up to 15W PD (data only))³

Multimedia

Modular Camera/Soundbar Support
Yes (Optional Support⁵)

Special Features

Software

LDFM (Lenovo Display Fleet Manager)

Lenovo ThinkColour (Lenovo Accessories
and Display Manager)⁶

Natural Low Blue Light
Yes

Power

Power Consumption (Typ. / Max.)
12.0W / 66.0W

Power Consumption Sleep/Off Mode
< 0.5W

Power Consumption Switch-Off Mode
< 0.3W

**ENERGY STAR Power Consumption
(Pon/E_{rec})**
11.6W / 38.6kWh

Power Supply
Internal

Voltage Required
AC 100 to 240 V (50-60Hz)

Mechanical

Tilt Angle (Front / Back)
-5° / 23.5°

Swivel Angle (Left / Right)
-45° / 45°

Lift (Max. Range)
155 mm

Pivot
-90° / 90°

VESA Mount Capability
Yes (100 x 100 mm)

ThinkCentre M Series Tiny Support
Yes, by ThinkCentre Tiny
Mounting Kit⁷ (PN: 4XF1R07369)

Kensington Nano Security Slot
Yes (2.5 mm x 6 mm)

Cable Management
Yes

Bezel Color
Eclipse Black

Bezel Width (Side)
2.0 mm

Bezel Width (Top)
2.0 mm

Bezel Width (Bottom)
10.5 mm

Dimension & Weight

**Size Packed
(W x D x H, mm/inch)**
734.0 x 112.0 x 422.0 mm
28.90 x 4.41 x 16.61 inches

**Size Unpacked w/ Stand
(Highest Position)
(W x D x H, mm/inch)**
539.8 x 190.0 x 505.8 mm
21.25 x 7.48 x 19.91 inches

**Size Unpacked w/ Stand
(Lowest Position)
(W x D x H, mm/inch)**
539.8 x 190.0 x 350.8 mm
21.25 x 7.48 x 13.81 inches

**Size Unpacked w/o Stand
(Head Only)
(W x D x H, mm/inch)**
539.8 x 45.3 x 314.8 mm
21.25 x 1.78 x 12.39 inches

Weight Packed (kg / lbs.)
7.3 kg / 16.1lbs.

Weight Unpacked (kg / lbs.)
5.1 kg / 11.2 lbs.

Weight (Head Only) (kg / lbs.)
3.0 kg / 6.6 lbs.

What's in the Box

Monitor with Stand
Yes

Power Cable (Cable Length)
1 x Power Cable (1.8 m)

DP Cable (Cable Length)
1 x DP 1.2 Cable (1.8 m)

USB Cable (Cable Length)
1 x USB Type-B to Type-A Gen 1 Cable
(1.8 m)

Quick Setup Guide
Yes

Certification

ENERGY STAR Certification
Yes

TCO
10

TCO Edge
2.1

EPEAT
Gold

**Volatile Organic Compound
Certification**
Yes

RoHS (2011/65/EU)
Yes

Windows Certification
Windows 10, Windows 11

EU Energy Level Certification
Yes (Level-C)

China Energy Efficiency Standard
Tier 1

TÜV Rheinland* Eye Comfort
5 Stars

**TÜV Rheinland* Low Blue Light
(Hardware Solution)**
Yes

Eyesafe Display Certification
Yes (Eyesafe 2.0)



¹ VRR as specified in HDMI 2.1, DRR for Microsoft Windows. | ² Supports 1920 x 1080 @ 120Hz as specified in HDMI 1.4. | ³ The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s; USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1) 5 Gbit/s; USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2) 10 Gbit/s; USB 4[®] 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps) 20 Gbit/s; USB4[®] 40Gbps (USB 40Gbps) 40 Gbit/s; Thunderbolt™ 3/4: 40 Gbit/s. | ⁴ USB Type-C and USB-C are registered trademarks of USB Implementers Forum. | ⁵ Compatible with ThinkVision VoIP Stack MC60 Monitor Webcam and MS30 Monitor Soundbar. | ⁶ Formerly Lenovo Display Control Center. Supports Windows 10 & 11, Mac OS (functions vary across systems). | ⁷ Sold separately. Need to assemble ThinkCentre Tiny mounting kit (PN: 4XF1R07369) to support Tiny PC installation.